

Package: ravedash (via r-universe)

October 23, 2026

Type Package

Title Dashboard for Reproducible Visualization of 'iEEG'

Version 0.1.3.56

Description Dashboard system to display the analysis results produced by 'RAVE', Magnotti J.F., Wang Z., Beauchamp M.S. (2020), <[doi:10.1016/j.neuroimage.2020.117341](https://doi.org/10.1016/j.neuroimage.2020.117341)>; see <<https://rave.wiki>> for more documentations. Provides infrastructure to integrate customized analysis pipelines into dashboard modules, including file structures, front-end widgets, and event handlers; see <<https://github.com/rave-ieeg/rave-pipelines>> for implementation details.

License MIT + file LICENSE

Encoding UTF-8

Language en-US

Imports grDevices, stats, dplyr (>= 0.2.0), ravel, ravelpipeline, rpy2 (>= 0.1.2), shdashi (>= 0.1.1), shiny (>= 1.7.1), shinyWidgets (>= 0.6.2), threeBrain (>= 0.2.4), shinyvalidate, R6, later, checkmate, cachem (>= 1.0.6)

Suggests cli, crayon (>= 1.4.2), htmltools, fastmap (>= 1.1.0), rlang (>= 1.0.2), rstudioapi, knitr, httr, rmarkdown, testthat (>= 3.0.0)

URL <https://dipterix.org/ravedash/>

BugReports <https://github.com/dipterix/ravedash/issues>

VignetteBuilder knitr

Config/testthat/edition 3

Config/roxygen2/version 8.1.0

Config/pak/sysreqs cmake libfftw3-dev git libglpk-dev make libicu-dev libpng-dev libuv1-dev libxml2-dev libssl-dev python3 libzmq3-dev zlib1g-dev

Repository <https://dipterix.r-universe.dev>

Date/Publication 2026-10-08 07:01:40 UTC

RemoteUrl <https://github.com/dipterix/ravedash>
RemoteRef HEAD
RemoteSha 457690d1872f5099e38345c7d5384a4fd0c95f82

Contents

card_url	2
check_new_repository_loaded	3
create_report_wizard	4
debug_modules	5
get_active_module_info	6
group_box	6
load_data_button	7
module_server_common	8
new_rave_shiny_component_container	10
obsolete	11
plotOutput2	12
random-text	12
rave-input-output-card	13
rave-runtime-events	15
rave-session	18
rave-ui-preset	21
ravedash_footer	26
run_analysis_button	27
safe_observe	28
safe_reactive	29
shiny_cache	30
shiny_check_input	31
shiny_icons	32
simple_layout	32
temp_file	34
with_error_notification	35
with_log_modal	36
Index	38

card_url	<i>Set 'URL' scheme for modules</i>
----------	-------------------------------------

Description

Automatically generates href for [input_card](#) and [output_card](#)

Usage

```
set_card_url_scheme(module_id, root, sep = "/")

card_href(title, type = "input", module_id = NULL)
```

Arguments

module_id	the module ID
root	'URL' default route
sep	separation
title	a title string that will be used to generate 'URL'
type	type of the card; choices are 'input' or 'output'

Value

The hyper reference of suggested card 'URL'

Examples

```
set_card_url_scheme(
  module_id = "power_explorer",
  root = "https://openwetware.org/wiki/RAVE:ravebuiltins",
  sep = ":")

card_href("Set Electrodes", type = "input", module_id = "power_explorer")
```

check_new_repository_loaded

Check whether repository read from pipeline has been updated

Description

Helper function to check if new pipeline repository is loaded; see 'Examples'

Usage

```
check_new_repository_loaded(
  component_container,
  pipeline,
  repository_class = NA,
  session = shiny::getDefaultReactiveDomain()
)
```

Arguments

component_container A 'RAVESHinyComponentContainer' instance
 pipeline A [pipeline](#) instance
 repository_class Expected repository class; default is arbitrary
 session A shiny session

Value

Logical TRUE or FALSE is new repository is loaded

Examples

```
## Not run:

shiny::bindEvent(
  ravedash::safe_observe({
    if (!ravedash::on_new_repository_loaded()) {
      return()
    }

    # Handle event when new repository is loaded

  }, priority = 1001),
  ravedash::watch_data_loaded(),
  ignoreNULL = FALSE,
  ignoreInit = FALSE
)

## End(Not run)
```

create_report_wizard *Create report wizard to be used within the interactive modules*

Description

Create report wizard to be used within the interactive modules

Usage

```
create_report_wizard(  
  pipeline,  
  session = shiny::getDefaultReactiveDomain(),  
  env = parent.frame()  
)
```

Arguments

pipeline	ravepipeline pipeline
session	shiny session
env	environment used to register the wizard inputs with shidashi , so that agents can choose and generate reports; default is the calling frame, typically the module server

Value

A list of functions: launch with argument subject to be called when users want to pop up a wizard allowing users to choose reports; generate with arguments subject and report_names to generate reports

debug_modules	<i>Debug 'RAVE' modules interactively in local project folder</i>
---------------	---

Description

Debug 'RAVE' modules interactively in local project folder

Usage

```
debug_modules(  
  module_root = rstudioapi::getActiveProject(),  
  host = "127.0.0.1",  
  port = 17283,  
  jupyter = FALSE,  
  ...  
)
```

Arguments

module_root	root of modules, usually the project folder created from 'shidashi' template
host, port	host and port of the application
jupyter	whether to launch 'Jupyter' server; default is false
...	passed to render

Value

'RStudio' job ID

get_active_module_info

Get current active module information, internally used

Description

Get current active module information, internally used

Usage

```
get_active_module_info(session = shiny::getDefaultReactiveDomain())
```

```
get_active_pipeline(session = shiny::getDefaultReactiveDomain())
```

Arguments

session shiny reactive domain, default is current domain

Value

A named list, including module ID, module label, internal 'rave_id'.

group_box

Group input elements into a box with title

Description

Only works in template framework provided by 'shidashi' package, see [use_template](#)

Usage

```
group_box(title, ..., class = NULL)
```

```
flex_group_box(title, ..., class = NULL, wrap = "wrap", direction = "row")
```

Arguments

title the box title
 ... elements to be included or to be passed to other methods
 class additional class of the box
 wrap, direction see [flex_container](#)

Value

A 'HTML' tag

Examples

```
library(shiny)
library(shidashi)
library(ravedash)

group_box(
  title = "Analysis Group A",
  selectInput("a", "Condition", choices = c("A", "B")),
  sliderInput("b", "Time range", min = 0, max = 1, value = c(0,1))
)

flex_group_box(
  title = "Project and Subject",
  flex_item( "Some input 1" ),
  flex_item( "Some input 2" ),
  flex_break(),
  flex_item( "Some input in new line" )
)
```

load_data_button	<i>Button to trigger data loader</i>
------------------	--------------------------------------

Description

A button that triggers 'load_data' event, which runs scripts registered via `set_script` with `binding_event = "load_data"` (see [module_server_common](#)); the same script can be triggered programmatically via `trigger_script`.

Usage

```
load_data_button(
  label = "Load data",
  icon = NULL,
  width = NULL,
  type = "primary",
  btn_type = c("button", "link"),
  class = "",
  style = "",
  ...
)
```

Arguments

label	label to display
icon	icon before the label
width, class, style, ...	passed to 'HTML' tag
type	used to calculate class
btn_type	button style, choices are 'button' or 'link'

Value

A 'HTML' button tag

See Also

[run_analysis_button](#), [get_rave_event](#)

Examples

```
# In loader UI
load_data_button("Load subject", width = "100%")

# In loader server function
## Not run:
server_tools <- get_default_handlers(session = session)
server_tools$set_script(
  "load_data",
  {
    # load data ...
  },
  binding_event = "load_data",
  dispatch_event = "data_changed",
  alert_params = list(title = "Loading in progress")
)

## End(Not run)
```

module_server_common	<i>Default module server function</i>
----------------------	---------------------------------------

Description

Common shiny server function to enable modules that requires data loader panel.

Usage

```
module_server_common(
  module_id,
  check_data_loaded,
  ...,
  session = shiny::getDefaultReactiveDomain(),
  parse_env = NULL
)
```

Arguments

module_id	'RAVE' module ID
check_data_loaded	a function that takes zero to one argument and must return either TRUE if data has been loaded or FALSE if loader needs to be open to load data.
...	ignored
session	shiny session; <code>init_app</code> must be called before this function so that the shidashi session registry is initialized.
parse_env	environment used to parse module

Value

A list of server utility functions; see 'Examples' below.

Examples

```
# 'RAVE' module server function
server <- function(input, output, session, ...) {
  shidashi::init_app()

  pipeline_path <- "PATH to module pipeline"

  module_server_common(
    module_id = session$ns(NULL),
    check_data_loaded = function(first_time) {

      re <- tryCatch({
        # Try to read data from pipeline results
        repo <- ravepipeline::pipeline_read(
          'repository',
          pipe_dir = pipeline_path
        )

        # Fire event to update footer message
        ravedash::fire_rave_event('loader_message',
                                "Data loaded")

        # Return TRUE indicating data has been loaded
        TRUE
      }, error = function(e) {
```

```

    # Fire event to remove footer message
    ravedash::fire_rave_event('loader_message', NULL)

    # Return FALSE indicating no data has been found
    FALSE
  })
}, session = session
)

# Register data loader script, triggered by `load_data_button()`
# in the loader UI, or by `server_tools$trigger_script("load_data")`
server_tools <- get_default_handlers(session = session)
server_tools$set_script(
  "load_data",
  {
    ravepipeline::pipeline_run(pipe_dir = pipeline_path,
                              names = "repository")
  },
  binding_event = "load_data",
  dispatch_event = "data_changed",
  alert_params = list(title = "Loading in progress")
)
}

```

```
new_rave_shiny_component_container
```

Creates a container for preset components

Description

Creates a container for preset components

Usage

```

new_rave_shiny_component_container(
  module_id,
  pipeline_name,
  pipeline_path = ravepipeline::pipeline_find(pipeline_name),
  settings_file = "settings.yaml"
)

```

Arguments

<code>module_id</code>	'RAVE' module ID
<code>pipeline_name</code>	the name of pipeline to run
<code>pipeline_path</code>	path of the pipeline

settings_file the settings file of the pipeline, usually stores the pipeline input information;
 default is "settings.yaml"

Value

A 'RAVShinyComponentContainer' instance

Examples

```
f <- tempfile()
dir.create(f, showWarnings = FALSE, recursive = TRUE)
file.create(file.path(f, "settings.yaml"))

container <- new_rave_shiny_component_container(
  module_id = "module_power_phase_coherence",
  pipeline_name = "power_phase_coherence_pipeline",
  pipeline_path = f
)

loader_project <- presets_loader_project()
loader_subject <- presets_loader_subject()

container$add_components(
  loader_project, loader_subject
)
```

obsolete	<i>Obsolete functions</i>
----------	---------------------------

Description

Reserved for compatibility; do not use.

Usage

```
output_gadget_container(expr, ..., quoted = FALSE, env = parent.frame())
```

Arguments

- | | |
|--------|------------------------------|
| expr | expression to evaluate |
| ... | ignored |
| quoted | whether expr is quoted |
| env | environment to evaluate expr |

`plotOutput2`*Shiny plot output with minimum height and additional classes*

Description

Shiny plot output with minimum height and additional classes

Usage

```
plotOutput2(  
  outputId,  
  class = NULL,  
  width = "100%",  
  height = "100%",  
  min_height = "400px",  
  ...  
)
```

Arguments

<code>outputId</code> , <code>width</code> , <code>height</code> , ...	passed to <code>plotOutput</code>
<code>class</code>	additional 'HTML' class of the output wrapper
<code>min_height</code>	minimum height of the image; default is 400 pixels

Value

A plot output element that can be included in a panel.

Examples

```
plotOutput2("plot", class = "rounded overflow-hidden",  
  min_height = 300)
```

`random-text`*Randomly choose a text from a list of strings*

Description

Randomly choose a text from a list of strings

Usage

```
be_patient_text(candidates)
```

```
finished_text(candidates)
```

Arguments

`candidates` character vectors, a list of candidates

Value

`be_patient_text` returns a text asking users to be patient; `finished_text` returns the text indicating the task has finished.

Examples

```
be_patient_text()
```

```
finished_text()
```

rave-input-output-card

Input and output card (front-end element)

Description

Input and output card (front-end element)

Usage

```
input_card(
  title,
  ...,
  class = "",
  class_header = "shidashi-anchor",
  class_body = "padding-10",
  class_foot = "padding-10",
  href = "auto",
  tools = NULL,
  footer = NULL,
  append_tools = TRUE,
  toggle_advanced = FALSE,
  module_id = get0("module_id", ifnotfound = NULL, envir = parent.frame())
)

output_card(
```

```

    title,
    ...,
    class = "",
    class_body = "padding-10",
    class_foot = "padding-10",
    href = "auto",
    tools = NULL,
    append_tools = TRUE,
    module_id = get0("module_id", ifnotfound = NULL, envir = parent.frame())
)

output_cardset(
  title,
  ...,
  class = "",
  class_body = "no-padding",
  class_foot = "padding-10",
  href = "auto",
  tools = NULL,
  append_tools = TRUE,
  module_id = get0("module_id", ifnotfound = NULL, envir = parent.frame())
)

```

Arguments

<code>title</code>	title of the card
<code>...</code>	additional elements to be included in the card, see card
<code>class</code>	the 'HTML' class for card
<code>class_header</code>	the 'HTML' class for card header; default is 'shidashi-anchor', which will generate shortcuts at the page footers
<code>class_body</code>	the 'HTML' class for card body; default is "padding-10", with '10px' at each direction
<code>class_foot</code>	the 'HTML' class for card footer; default is "padding-10", with '10px' at each direction
<code>href</code>	hyper reference link of the card
<code>tools</code>	a list of additional card tools, see card_tool
<code>footer</code>	footer elements
<code>append_tools</code>	whether to append tools to the default list; default is true
<code>toggle_advanced</code>	whether to show links in the footer to toggle elements with 'HTML' class 'rave-optional'
<code>module_id</code>	the 'RAVE' module ID

Value

'HTML' tags

See Also[card](#)**Examples**

```
input_card(title = "Condition selector",
           "Please select experimental conditions:",
           shiny::selectInput(
             inputId = "condition", label = "Condition",
             choices = c("Audio", "Visual")
           ))
```

rave-runtime-events	<i>'RAVE' run-time events</i>
---------------------	-------------------------------

Description

A set of preset behaviors used by 'RAVE' modules

Usage

```
register_rave_session(
  session = shiny::getDefaultReactiveDomain(),
  .rave_id = NULL
)

get_default_handlers(session = shiny::getDefaultReactiveDomain())

fire_rave_event(
  key,
  value,
  global = FALSE,
  force = FALSE,
  session = shiny::getDefaultReactiveDomain(),
  .internal_ok = FALSE
)

get_rave_event(key, session = shiny::getDefaultReactiveDomain())

open_loader(session = shiny::getDefaultReactiveDomain())

close_loader(session = shiny::getDefaultReactiveDomain())

watch_loader_opened(session = shiny::getDefaultReactiveDomain())
```

```
watch_data_loaded(session = shiny::getDefaultReactiveDomain())

current_shiny_theme(default, session = shiny::getDefaultReactiveDomain())
```

Arguments

<code>session</code>	shiny session, usually automatically determined
<code>key</code>	event key to fire or to monitor
<code>value</code>	event value
<code>global</code>	whether to notify other sessions (experimental and not recommended)
<code>force</code>	whether to force firing the event even the value hasn't changed
<code>.internal_ok</code>	internally used
<code>default</code>	default value if not found
<code>rave_id, .rave_id</code>	deprecated, no longer used

Details

These goal of these event functions is to simplify the dashboard logic without understanding the details or passing global variables around. Everything starts with `shidashi::register_session`. This function registers session event handlers and theme observers. If you have called `module_server_common`, then session registration has already been done.

`register_rave_session` **Deprecated.** Use `shidashi::register_session()` instead.

`fire_rave_event` send signals to make changes to a event; returns nothing

`get_rave_event` watch and get the event values; must run in shiny reactive context

`open_loader` fire an event with a special key 'open_loader' to open the data-loading panel; returns nothing

`close_loader` reset an event with a special key 'open_loader' to close the data-loading panel if possible; returns nothing

`watch_loader_opened` watch in shiny reactive context whether the loader is opened; returns a logical value, but raise errors when reactive context is missing

`watch_data_loaded` watch a special event with key 'data_loaded'; returns a logical value of whether new data has been loaded, or raise errors when reactive context is missing

`current_shiny_theme` watch and returns a list of theme parameters, for example, light or dark theme

Value

See 'Details'

Built-in Events

The following event keys are built-in. Please do not fire them using `fire_rave_event` or the 'RAVE' application might will crash

'simplify_toggle' toggle visibility of 'HTML' elements with class 'rave-option'

'run_analysis' notifies the module to run pipeline

'load_data' notifies the module to run scripts registered with `binding_event = "load_data"`;
see [load_data_button](#)

'save_pipeline', 'load_pipeline' notifies the module to save or load pipeline

'data_loaded' notifies the module that new data has been loaded

'open_loader', 'toggle_loader' notifies the internal server code to show or hide the data loading panel

'active_module' internally populated by the action dispatcher when the module first loads (and whenever a type = "active_module" rave-action arrives). Returns a list with elements type, id, parent_frame, and rave_id. This key is **reserved**: external code must not call `fire_rave_event("active_module")` directly. To obtain the currently active module, prefer [get_active_module_info\(\)](#), which reads from the shidashi module registry and is always up-to-date.

Examples

```
library(shiny)
library(ravedash)

ui <- fluidPage(
  actionButton("btn", "Fire event"),
  actionButton("btn2", "Toggle loader")
)

server <- function(input, output, session) {
  # Create event registries
  shidashi::register_session()

  shiny::bindEvent(
    shiny::observe({
      fire_rave_event("my_event_key", Sys.time())
    }),
    input$btn,
    ignoreInit = TRUE,
    ignoreNULL = TRUE
  )
  shiny::bindEvent(
    shiny::observe({
      cat("An event fired with value:", get_rave_event("my_event_key"), "\n")
    }),
    get_rave_event("my_event_key"),
    ignoreNULL = TRUE
  )
}
```

```

shiny::bindEvent(
  shiny::observe({
    if (watch_loader_opened()) {
      close_loader()
    } else {
      open_loader()
    }
  }),
  input$btn2,
  ignoreInit = TRUE,
  ignoreNULL = TRUE
)

shiny::bindEvent(
  shiny::observe({
    cat("Loader ", ifelse(watch_loader_opened(), "opened", "closed"), "\n")
  }),
  watch_loader_opened(),
  ignoreNULL = TRUE
)

}

if(interactive()) {
  shinyApp(ui, server)
}

```

rave-session

Create, register, list, and remove 'RAVE' sessions

Description

Create, register, list, and remove 'RAVE' sessions

Usage

```
new_session(update = FALSE, app_root = NULL)
```

```
use_session(x, ...)
```

```

launch_session(
  x,
  host = "127.0.0.1",
  port = NULL,
  modules = NULL,
  dry_run = FALSE,
  options = list(jupyter = TRUE, jupyter_port = NULL, as_job = TRUE, launch_browser =
    TRUE, single_session = FALSE, page_title = NULL, sidebar_open = TRUE)
)

```

```

)

session_getopt(keys, default = NA, namespace = "default")

session_setopt(..., .list = NULL, namespace = "default")

remove_session(x)

remove_all_sessions()

list_session(path = session_root(), order = c("none", "ascend", "descend"))

start_session(
  session,
  new = NA,
  modules = NULL,
  page_title = NULL,
  sidebar_open = TRUE,
  host = "127.0.0.1",
  port = NULL,
  jupyter = NA,
  jupyter_port = NULL,
  as_job = TRUE,
  launch_browser = TRUE,
  single_session = FALSE,
  app_root = NULL,
  dry_run = FALSE
)

shutdown_session(
  returnValue = invisible(NULL),
  jupyter = TRUE,
  session = shiny::getDefaultReactiveDomain()
)

session_log(x, max_lines = 200, modules = NULL)

```

Arguments

update	logical, whether to update to latest 'RAVE' template
..., .list	named list of key-value pairs of session options. The keys must be characters, and values must be simple data types (such as numeric vectors, characters)
host	host 'IP' address, default is 'localhost'
port	port to listen
modules	selected module ID to launch; used to only show a subset of modules; default is NULL (select all modules); hidden modules are always selected
dry_run	whether to dry-run (do not launch) the 'RAVE' session

options	additional options, including jupyter, jupyter_port, as_job, and launch_browser
keys	vector of characters, one or more keys of which the values should be obtained
default	default value if key is missing
namespace	namespace of the option; default is 'default'
path, app_root	root path to store the sessions; default is the "tensor_temp_path" in raveio_getopt
order	whether to order the session by date created; choices are 'none' (default), 'ascend', 'descend'
session, x	session identification string, or session object; use <code>list_session</code> to list all existing sessions
new	whether to create a new session instead of using the most recent one, default is false
page_title	session web page title and logo text; can have length of either one (page title and logo text are the same); or length of two, with page title be the first element and logo text be the second.
sidebar_open	whether to open the side-bar by default; default TRUE when more than one module is to be displayed
jupyter	logical, whether to launch 'jupyter' instances when starting 'RAVE' sessions, or to stop the 'jupyter' instances when shutting down. It requires additional setups to enable 'jupyter' lab; see 'Installation Guide Step 3' in the 'RAVE' wiki page.
jupyter_port	port used by 'jupyter' lab, can be set by 'jupyter_port' option in raveio_setopt
as_job	whether to launch the application as 'RStudio' job, default is true if 'RStudio' is detected; when running without 'RStudio', this option is always false
launch_browser	whether to launch browser, default is true
single_session	whether to enable single-session mode. Under this mode, closing the main frame will terminate 'RAVE' run-time session, otherwise the 'RAVE' instance will still open in the background
returnValue	passed to stopApp
max_lines	maximum number of log entries to return; default is 200

Value

`new_session` returns a session object with character 'session_id' and a function 'launch_session' to launch the application from this session

`use_session` returns a session object, the same as `new_session` under the condition that corresponding session exists, or raise an error if the session is missing

`list_session` returns a list of all existing session objects under the session root

`remove_session` returns a logical whether the corresponding session has been found and removed

Examples

```
if (interactive()) {
  sess <- new_session()
```

```

    sess$launch_session()

    all_sessions <- list_session()
    print(all_sessions)

    # Use existing session
    session_id <- all_sessions[[1]]$session_id
    sess <- use_session(session_id)
    sess$launch_session()

    # Remove session
    remove_session(session_id)
    list_session()
  }

```

rave-ui-preset

Preset reusable front-end components for 'RAVE' modules

Description

For examples and use cases, please check [new_rave_shiny_component_container](#).

Usage

```

presets_analysis_electrode_selector2(
  id = "electrode_text",
  varname = "analysis_electrodes",
  label = "Select Electrodes",
  loader_project_id = "loader_project_name",
  loader_subject_id = "loader_subject_code",
  pipeline_repository = "repository",
  start_simple = FALSE,
  multiple = TRUE,
  hint = NULL,
  env = parent.frame()
)

presets_analysis_ranges(
  id = "analysis_ranges",
  varname = "analysis_ranges",
  label = "Configure Analysis",
  pipeline_repository = "repository",
  max_components = 2,
  hint = NULL,
  env = parent.frame()
)

```

```

presets_baseline_choices(
    id = "baseline_choices",
    varname = "baseline",
    label = "Baseline Settings",
    pipeline_repository = "repository",
    baseline_choices = c("Decibel", "% Change Power", "% Change Amplitude",
        "z-score Decibel", "z-score Power", "z-score Amplitude"),
    baseline_along_choices = c("Per frequency, trial, and electrode", "Across electrode",
        "Across trial", "Across trial and electrode"),
    hint = NULL,
    env = parent.frame()
)

presets_condition_groups(
    id = "condition_groups",
    varname = "condition_groups",
    label = "Create Condition Contrast",
    pipeline_repository = "repository",
    hint = NULL,
    env = parent.frame()
)

presets_import_export_subject_pipeline(
    id = "im_ex_pipeline",
    loader_project_id = "loader_project_name",
    loader_subject_id = "loader_subject_code",
    pipeline_repository = "repository",
    settings_entries = c("loaded_electrodes", "epoch_choice", "epoch_choice__trial_starts",
        "epoch_choice__trial_ends", "reference_name"),
    fork_mode = c("exclude", "include")
)

presets_import_setup_blocks(
    id = "import_blocks",
    label = "Format & session blocks",
    import_setup_id = "import_setup",
    max_components = 5,
    env = parent.frame()
)

presets_import_setup_native(
    id = "import_setup",
    label = "Select project & subject",
    env = parent.frame()
)

presets_loader_3dviewer(
    id = "loader_3d_viewer",

```

```
        height = "600px",
        loader_project_id = "loader_project_name",
        loader_subject_id = "loader_subject_code",
        loader_reference_id = "loader_reference_name",
        loader_electrodes_id = "loader_electrode_text",
        ...
    )

presets_loader_3dviewer2(
    id = "loader_3d_viewer",
    height = "600px",
    loader_project_id = "loader_project_name",
    loader_subject_id = "loader_subject_code",
    loader_electrodes_id = "loader_electrode_text",
    ...
)

presets_loader_electrodes(
    id = "loader_electrode_text",
    varname = "loaded_electrodes",
    label = "Electrodes",
    loader_project_id = "loader_project_name",
    loader_subject_id = "loader_subject_code",
    hint = NULL,
    env = parent.frame()
)

presets_loader_epoch(
    id = "loader_epoch_name",
    varname = "epoch_choice",
    label = "Epoch and Trial Duration",
    loader_project_id = "loader_project_name",
    loader_subject_id = "loader_subject_code",
    allow_stitch = FALSE,
    hint = NULL,
    env = parent.frame()
)

presets_loader_project(
    id = "loader_project_name",
    varname = "project_name",
    label = "Project",
    hint = NULL,
    env = parent.frame()
)

presets_loader_reference(
    id = "loader_reference_name",
```

```

    varname = "reference_name",
    label = "Reference name",
    loader_project_id = "loader_project_name",
    loader_subject_id = "loader_subject_code",
    mode = c("default", "create"),
    hint = NULL,
    env = parent.frame()
)

presets_loader_subject(
  id = "loader_subject_code",
  varname = "subject_code",
  label = "Subject",
  loader_project_id = "loader_project_name",
  checks = c("notch", "wavelet"),
  allow_new = FALSE,
  hint = NULL,
  env = parent.frame()
)

presets_loader_subject_only(
  id = "loader_subject_code",
  varname = "subject_code",
  label = "Subject",
  multiple = FALSE,
  hint = NULL,
  env = parent.frame()
)

presets_loader_sync_project_subject(
  id = "loader_sync_project_subject",
  label = "Sync subject from most recently loaded",
  varname = "loader_sync_project_subject",
  loader_project_id = "loader_project_name",
  loader_subject_id = "loader_subject_code",
  from_module = NULL,
  project_varname = "project_name",
  subject_varname = "subject_code"
)

```

Arguments

<code>id</code>	input or output ID of the element; this ID will be prepended with module namespace
<code>varname</code>	variable name(s) in the module's settings file
<code>label</code>	readable label(s) of the element
<code>loader_project_id</code>	the ID of <code>presets_loader_project</code> if different to the default

loader_subject_id	the ID of presets_loader_subject if different to the default
pipeline_repository	the pipeline name that represents the 'RAVE' repository from functions such as prepare_subject_bare , prepare_subject_with_epochs , and prepare_subject_power
start_simple	whether to start in simple view and hide optional inputs
multiple	whether to allow multiple inputs
hint	hints for agents (see <code>shidashi::input_hint_classes</code>): whether they ask the user for an input before loading data or running the analysis, keep its default, or leave it alone. Each preset has its own defaults (for example, loader inputs are "loader_mandatory"); give one unnamed value for every input of the preset, or values named by input ID to override some of them, for example <code>c(loader_epoch_name__trial_starts = "loader_optional")</code>
env	environment in which the preset is created; default is the calling frame, typically the module environment where the module scripts are sourced. shidashi looks up the module's input registry from this environment, so that agents can query and update the preset inputs
max_components	maximum number of components for compound inputs
baseline_choices	the possible approaches to calculate baseline
baseline_along_choices	the units of baseline
settings_entries	used when importing pipelines, pipeline variable names to be included or excluded, depending on fork_mode
fork_mode	'exclude' (default) or 'include'; in 'exclude' mode, settings_entries will be excluded from the pipeline settings; in 'include' mode, only settings_entries can be imported.
import_setup_id	the ID of presets_import_setup_native if different to the default
height	height of the element
loader_reference_id	the ID of presets_loader_reference if different to the default
loader_electrodes_id	the ID of presets_loader_electrodes if different to the default
...	ignored, typically reserved for obsolete arguments
allow_stitch	whether to allow stitching the events
mode	whether to create new reference, or simply to choose from existing references
checks	whether to check if subject has been applied with 'Notch' filters or 'Wavelet'; default is both.
allow_new	whether to allow new subject to be created; ignored when checks exist
from_module	which module to extract input settings
project_varname, subject_varname	variable names that should be extracted from the settings file

Value

A 'RAVESHinyComponent' instance.

See Also

[new_rave_shiny_component_container](#)

ravedash_footer	<i>A hovering footer at bottom-right</i>
-----------------	--

Description

Internally used. Do not call explicitly

Usage

```
ravedash_footer(
  module_id = NULL,
  label = "Run Analysis",
  auto_recalculation = TRUE,
  message_action = "toggle_loader",
  class = NULL,
  style = NULL
)
```

Arguments

module_id	'RAVE' module ID
label	run-analysis button label; default is "Run Analysis"
auto_recalculation	whether to show the automatic calculation button; default is true
message_action	message to send when clicking on message button; default is 'toggle_loader', which opens up loading screen
class	additional class for the footer
style	additional style for the footer

Value

'HTML' tags

Examples

```

library(shiny)
# dummy variables for the example
data_loaded <- TRUE

# UI code
ravedash_footer("my_module")

# server code to set message
server <- function(input, output, session) {

  module_server_common(input, output, session, function() {

    # check if data has been loaded
    if (data_loaded) {

      # if yes, then set the footer message
      fire_rave_event("loader_message",
                     "my_project/subject - Epoch: Auditory")
      return(TRUE)
    } else {

      # No data found, unset the footer message
      fire_rave_event("loader_message", NULL)
      return(FALSE)
    }

  })
}

```

run_analysis_button *Button to trigger analysis*

Description

A button that triggers 'run_analysis' event; see also [get_rave_event](#)

Usage

```

run_analysis_button(
  label = "Run analysis (Ctrl+Enter)",
  icon = NULL,
  width = NULL,
  type = "primary",
  btn_type = c("button", "link"),
  class = "",
  style = "",
  ...
)

```

Arguments

label	label to display
icon	icon before the label
width, class, style, ...	passed to 'HTML' tag
type	used to calculate class
btn_type	button style, choices are 'button' or 'link'

Value

A 'HTML' button tag

safe_observe	<i>Safe-wrapper of 'shiny' observe function</i>
--------------	---

Description

Safely wrap expression x such that shiny application does no hang when when the expression raises error.

Usage

```
safe_observe(
  x,
  env = NULL,
  quoted = FALSE,
  priority = 0L,
  domain = NULL,
  ...,
  error_wrapper = c("none", "notification", "alert"),
  watch_data = getOption("ravedash.auto_watch_data", FALSE)
)
```

Arguments

x, env, quoted, priority, domain, ...	passed to observe
error_wrapper	handler when error is encountered, choices are 'none', 'notification' (see error_notification), or 'alert' (see error_alert)
watch_data	whether to invalidate only when watch_data_loaded is TRUE

Value

'shiny' observer instance

Examples

```
values <- shiny::reactiveValues(A=1)

obsB <- safe_observe({
  print(values$A + 1)
})
```

safe_reactive

Safe-wrapper of 'shiny' [reactive](#) function

Description

A reactive expression whose errors never reach its consumers: an error is logged (and optionally shown) and the expression yields the last value it produced, or initial before its first success. Validation errors ([req](#), [validate](#)) pass through, so outputs still stop rendering as they do with [reactive](#).

Usage

```
safe_reactive(
  x,
  env = parent.frame(),
  quoted = FALSE,
  ...,
  label = NULL,
  domain = shiny::getDefaultReactiveDomain(),
  initial = NULL,
  error_wrapper = c("none", "notification", "alert")
)
```

Arguments

x, env, quoted, label, domain, ...	passed to reactive
initial	value returned while no evaluation has succeeded yet
error_wrapper	handler when error is encountered, choices are 'none' (log only), 'notification' (see error_notification), or 'alert' (see error_alert)

Details

'shiny' caches the error raised by a reactive expression and raises it again to every consumer until the expression is invalidated; when the consumer is an observer, or the expression is a trigger of [bindEvent](#), the session is closed. The last good value therefore lives in this wrapper, not in the cache of the reactive expression.

Value

'shiny' reactive expression

Examples

```
values <- shiny::reactiveValues(A = 1)

doubled <- safe_reactive({
  if (values$A < 0) { stop("A must be non-negative") }
  values$A * 2
})

# In a running app, `doubled()` keeps its last value when `values$A` turns
# negative; the error goes to the log instead of closing the session
```

shiny_cache

Obtain caching object for current run-time shiny session

Description

Deprecated. This function is no longer used by RAVE modules.

Cache small objects such as inputs or configurations.

Usage

```
shiny_cache(namespace, session = shiny::getDefaultReactiveDomain())
```

Arguments

namespace	characters, usually the module ID
session	shiny interactive context domain

Value

A caching object. The caching object is identical within the same context and namespace.

shiny_check_input	<i>Check shiny inputs and modify if validation fails</i>
-------------------	--

Description

Check shiny inputs and modify if validation fails

Usage

```
shiny_check_input(
  inputId,
  check = NULL,
  on_check_fails,
  ...,
  quoted = FALSE,
  env = parent.frame(),
  logger_level = c("trace", "none", "debug", "info", "warning", "error"),
  session = shiny::getDefaultReactiveDomain()
)
```

Arguments

inputId	character, input ID
check	either a function that takes the input value or a character of a checkmate function; when check is a character, this function will look for check_* functions in the checkmate package
on_check_fails	value to substitute when check fails, and the input value will be the result of on_check_fails. This argument can be missing; when missing, input value will not be altered
...	passed to check function
quoted	whether on_check_fails is quoted
env	environment to evaluate on_check_fails
logger_level	log level when validation fails
session	shiny session; default is current session

Value

A shiny observe instance

Examples

```
if(interactive()) {
  library(ravedash)
  shiny::shinyApp(
    ui = shiny::basicPage(
```

```
    shiny::textInput("id1", "Enter a text"),
    shiny::textOutput("id2")
  ),
  server = function(input, output, session) {
    # input$id1 must have at least 1 character
    # the check uses `checkmate::check_character`
    shiny_check_input(
      "id1",
      check = "character",
      min.chars = 1,
      on_check_fails = "altered text"
    )

    output$id2 <- shiny::renderText({
      print(input$id1)
      sprintf("The final value is: %s", input$id1)
    })
  }
}
```

shiny_icons	<i>Shiny icons</i>
-------------	--------------------

Description

Shiny icons

Usage

shiny_icons

Details

The goal of create this list is to keep 'shiny' icons (which are essentially 'font-awesome' icons) up-to-date.

simple_layout	<i>Simple input-output layout</i>
---------------	-----------------------------------

Description

Provides simple layout, with inputs on the left, and outputs on the right. Only useful in 'shidashi' framework.

Usage

```
simple_layout(  
  input_ui,  
  output_ui,  
  input_width = 4L,  
  container_fixed = FALSE,  
  container_style = NULL,  
  scroll = FALSE  
)
```

Arguments

input_ui	the 'HTML' tags for the inputs
output_ui	the 'HTML' tags for the outputs
input_width	width of inputs, must be an integer from 1 to 11
container_fixed	whether the maximum width of the container should be fixed; default is no
container_style	additional 'CSS' style of the container
scroll	whether to stretch the container to full-heights and scroll the input and output separately.

Value

'HTML' tags

Examples

```
library(shiny)  
library(ravedash)  
  
simple_layout(  
  input_ui = list(  
    ravedash::input_card(  
      title = "Data Selection",  
      "Add inputs here"  
    )  
  ),  
  output_ui = list(  
    ravedash::output_card(  
      title = "Result A",  
      "Add outputs here"  
    )  
  )  
)
```

temp_file	Create a random temporary file path for current session
-----------	---

Description

Create a random temporary file path for current session

Usage

```
temp_file(
  pattern = "file",
  fileext = "",
  persist = c("process", "app-session", "package-cache")
)

temp_dir(check = FALSE, persist = c("process", "app-session", "package-cache"))
```

Arguments

pattern, fileext	see tempfile
persist	persist level, choices are 'app-session', 'package-cache', and 'process'; see 'Details'. 'RAVE' application session, default), 'package-cache' (package-level cache directory)
check	whether to create the temporary directory

Details

R default [tempdir](#) usually gets removed once the R process ends. This behavior might not meet all the needs for 'RAVE' modules. For example, some data are 'RAVE' session-based, like current or last visited subject, project, or state data (like bookmarks, configurations). This session-based information will be useful when launching the same 'RAVE' instance next time, hence should not be removed when users close R. Other data, such as subject-related, or package-related should last even longer. These types of data may be cache of subject power, package-generated color schemes, often irrelevant from R or 'RAVE' sessions, and can be shared across different 'RAVE' instances.

The default scheme is `persist='process'`. Under this mode, this function behaves the same as [tempfile](#). To store data in 'RAVE' session-based manner, please use `persist='app-session'`. The actual path will be inside of 'RAVE' session folder, hence this option is valid only if 'RAVE' instance is running. When 'RAVE' instance is not running, the result falls back to `persist='process'`. When `persist='process'`, To cache larger and session-irrelevant data, use 'package-cache'.

The 'RAVE' session and package cache are not cleared even when R process ends. Users need to clean the data by themselves. See [remove_session](#) or [remove_all_sessions](#) about removing session-based folders, or [clear_cached_files](#) to remove package-based cache.

Value

A file or a directory path to persist temporary data cache

Examples

```
temp_dir()
temp_dir(persist = "package-cache")
```

```
with_error_notification
```

Evaluate with automatic error handlers in dashboard

Description

Keep track of messages printed by modules

Usage

```
error_notification(
  cond,
  title = "Error found!",
  type = "danger",
  class = "error_notif",
  delay = 30000,
  autohide = TRUE,
  collapse = "\n",
  prefix = paste("Found the following error",
    "(details have been printed in the console):"),
  session = shiny::getDefaultReactiveDomain()
)

error_alert(
  cond,
  title = "Error found!",
  type = "error",
  danger_mode = TRUE,
  auto_close = FALSE,
  prefix = paste("Found the following error",
    "(details have been printed in the console):"),
  buttons = "Confirm",
  session = shiny::getDefaultReactiveDomain()
)

with_error_notification(expr, envir = parent.frame(), quoted = FALSE, ...)

with_error_alert(expr, envir = parent.frame(), quoted = FALSE, ...)
```

Arguments

cond	condition to log
type	which type of logging should be set; default is 'console', if file log is enabled through <code>set_logger_path</code> , type could be 'file' or 'both'. Default log level is 'info' on console and 'debug' on file.
class, title, delay, autohide	passed to <code>show_notification</code>
collapse, danger_mode, auto_close, buttons	will be passed to <code>shiny_alert2</code> or <code>show_notification</code>
prefix	additional messages to display in the notification or alert
session	shiny session
expr	expression to evaluate
envir	environment to evaluate expr
quoted	whether expr is quoted; default is false
...	passed to other methods

Value

The condition cond if errors out, or the evaluated results

with_log_modal	<i>Evaluate script in the background and show the results from shiny modal dialogue</i>
----------------	---

Description

Evaluate script in the background and show the results from shiny modal dialogue

Usage

```
with_log_modal(
  expr,
  quoted = FALSE,
  callback = NULL,
  title = "Running...",
  size = "l",
  session = shiny::getDefaultReactiveDomain(),
  ...
)
```

Arguments

<code>expr</code>	R expression to evaluate The script must be standalone
<code>quoted</code>	whether the expression has been quoted
<code>callback</code>	callback function to run once the evaluate finishes; must take one argument. The passed variable will be the evaluation results or an error condition (if error occurs)
<code>title, size</code>	modal title and size, see showModal
<code>session</code>	shiny session object
<code>...</code>	ignored, reserved for future use

Value

A promise object

Examples

```
# Shiny server function
server <- function(input, output, session) {
  shiny::bindEvent(
    shiny::observe({
      with_log_modal(
        title = "Roll the dice",
        expr = {
          for(i in 1:10) {
            Sys.sleep(runif(1, min = 0.5, max = 2))
            cat(sprintf("Rolling dice result: %.0f\n", sample(6, 1)))
          }
        }
      )
    })
  return()
},
input$btn,
ignoreNULL = TRUE, ignoreInit = TRUE
)
}

if(interactive()) {
  shiny::shinyApp(
    ui = shiny::basicPage(
      shiny::actionButton('btn', "Click me")
    ),
    server = server,
    options = list(launch.browser = TRUE)
  )
}
```

Index

be_patient_text (random-text), 12
bindEvent, 29

card, 14, 15
card_href (card_url), 2
card_tool, 14
card_url, 2
check_new_repository_loaded, 3
clear_cached_files, 34
close_loader (rave-runtime-events), 15
create_report_wizard, 4
current_shiny_theme
 (rave-runtime-events), 15

debug_modules, 5

error_alert, 28, 29
error_alert (with_error_notification),
 35
error_notification, 28, 29
error_notification
 (with_error_notification), 35

finished_text (random-text), 12
fire_rave_event (rave-runtime-events),
 15
flex_container, 6
flex_group_box (group_box), 6

get_active_module_info, 6, 17
get_active_pipeline
 (get_active_module_info), 6
get_default_handlers
 (rave-runtime-events), 15
get_rave_event, 8, 27
get_rave_event (rave-runtime-events), 15
group_box, 6

init_app, 9
input_card, 2
input_card (rave-input-output-card), 13

launch_session (rave-session), 18
list_session (rave-session), 18
load_data_button, 7, 17

module_server_common, 7, 8, 16

new_rave_shiny_component_container, 10,
 21, 26
new_session (rave-session), 18

observe, 28
obsolete, 11
open_loader (rave-runtime-events), 15
output_card, 2
output_card (rave-input-output-card), 13
output_cardset
 (rave-input-output-card), 13
output_gadget_container (obsolete), 11

pipeline, 4
plotOutput, 12
plotOutput2, 12
prepare_subject_bare, 25
prepare_subject_power, 25
prepare_subject_with_epochs, 25
presets_analysis_electrode_selector2
 (rave-ui-preset), 21
presets_analysis_ranges
 (rave-ui-preset), 21
presets_baseline_choices
 (rave-ui-preset), 21
presets_condition_groups
 (rave-ui-preset), 21
presets_import_export_subject_pipeline
 (rave-ui-preset), 21
presets_import_setup_blocks
 (rave-ui-preset), 21
presets_import_setup_native
 (rave-ui-preset), 21
presets_loader_3dviewer
 (rave-ui-preset), 21

presets_loader_3dviewer2
 (rave-ui-preset), 21
presets_loader_electrodes
 (rave-ui-preset), 21
presets_loader_epoch (rave-ui-preset),
 21
presets_loader_project
 (rave-ui-preset), 21
presets_loader_reference
 (rave-ui-preset), 21
presets_loader_subject
 (rave-ui-preset), 21
presets_loader_subject_only
 (rave-ui-preset), 21
presets_loader_sync_project_subject
 (rave-ui-preset), 21

random-text, 12
rave-input-output-card, 13
rave-runtime-events, 15
rave-session, 18
rave-ui-preset, 21
ravedash_footer, 26
raveio_getopt, 20
raveio_setopt, 20
reactive, 29
register_rave_session
 (rave-runtime-events), 15
remove_all_sessions, 34
remove_all_sessions (rave-session), 18
remove_session, 34
remove_session (rave-session), 18
render, 5
req, 29
run_analysis_button, 8, 27

safe_observe, 28
safe_reactive, 29
session_getopt (rave-session), 18
session_log (rave-session), 18
session_setopt (rave-session), 18
set_card_url_scheme (card_url), 2
shiny_alert2, 36
shiny_cache, 30
shiny_check_input, 31
shiny_icons, 32
show_notification, 36
showModal, 37
shutdown_session (rave-session), 18

simple_layout, 32
start_session (rave-session), 18
stopApp, 20

temp_dir (temp_file), 34
temp_file, 34
tempdir, 34
tempfile, 34

use_session (rave-session), 18
use_template, 6

validate, 29

watch_data_loaded, 28
watch_data_loaded
 (rave-runtime-events), 15
watch_loader_opened
 (rave-runtime-events), 15
with_error_alert
 (with_error_notification), 35
with_error_notification, 35
with_log_modal, 36